



Point 115

The Point 115 Sub has been designed to complement the Point 8 enclosure; its width matching the height of the Point 8 - it can be horizontally mounted under the Point 115 Sub. The Point 115 Sub can also be used as a stand-alone product, paired with your existing system to supplement any missing bottom-end. This Active / Passive cabinet is extremely light weight - 38.5 lbs without crossover, and 43.5 lbs with a crossover. The Point 115 Sub is also available with all SLR™ rigging systems for the Point Series, thus arraying the cabinet is a breeze in any set-up, in any venue.

Specifications

Frequency Range (+/- 3dB)	55Hz - 200Hz
Components LF	ND15-S 15" Kevlar Neodymium Driver
Nominal Impedance LF	8 Ω
Power Handling (AES / Peak) LF	500 / 2000 W
Rigging	SLR™ Sockets, OmniMount 60 Series
Connection	2x Speakon™ NL4 (Barrier Strip Optional)
Height Front (mm / in)	419 / 16.5
Width (mm / in)	451 / 17.75
Depth (mm / in)	334 / 13.13
Weight (kg / lbs)	17.5 / 38.5 Active, 19.8 / 43.5 Passive
Processing	Lake, XTA

**12 dB crest factor pink noise at 1m, half space, using specified processing and amplification

