



PC 10

The Point Concentric 10 is the largest, most high powered enclosure with a conical dispersion pattern in the Point Concentric series. It is a compact, passive coaxial loudspeaker housing a single 10" component, featuring a 70° conical pattern. The enclosure produces linear, high-resolution audio throughout the intended bandwidth, and it includes three M10 fly points and one Omni Mount 30 series mounting point as well as a built-in polemount socket.

The PC 10 makes an excellent addition to your inventory as a powerful standalone solution for lighter audio reinforcement, or as a light-weight fill speaker, with a variety of rigging options.

All Point Concentric enclosures are constructed of 12 mm Baltic Birch, rather than moulded plastic or fiberglass, resulting in a lower resonant frequency.

Specifications

Frequency Range (-10 dB)	73 Hz - 18 kHz
Nominal Directivity (-6 dB) H x V	70° x 70°
Maximum Peak SPL**	132 dB
Components LMF / HF	B&C 10FCX64 10" Coaxial Driver
Nominal Impedance Passive	4 Ω
Power Handling (AES / Peak) LF	250 / 1000 W
Power Handling (AES / Peak) HF	80 / 320 W
Power Handling (AES / Peak) Passive	330 / 1320 W
Rigging	3x Mini SLR™ Socket (M10), Omni Mount 30 Series with 1/4 - 20 Screws, Built-in Polemount Socket
Connection	2x Speakon™ NL4
Height Front (mm / in)	387 / 15.24
Width (mm / in)	302 / 11.89
Depth (mm / in)	292 / 11.49
Weight (kg / lbs)	11.4 / 25
Processing	IPD

**12 dB crest factor pink noise at 1m, free field, using specified processing and amplification

